

AGCO NT01 Display Setup

Challenger NT01 display name = AccuTerminal

Fendt NT01 display name = VarioTerminal

Gleaner NT01 display name = Tyton

For:

2017 Gleaner S9* and newer

2017 RoGator C* series and newer

2017 FT 500/700/800/900/1000

2018 TerraGator C* series and newer

2018 Challenger 1000 and newer

2018 Challenger MT700 and newer

2018 Fendt IDEAL combine and newer

2018 CH MT600E wheeled tractor

2018 CH MT700

***Note: Pins 4 (red) & 5 (brown) on AGCO of BN2027 adapter need to be interchanged for RoGator, TerraGator, & Gleaner**

Receiver screen may appear differently than the following screenshots depending on receiver type (NovAtel or Trimble 382)

1

Install the Beacon & AGCO adapter. Use port X5130 behind the radio knockout on RoGator, TerraGator, & Gleaner.



2

On the Fendt & Challenger series, it is located on the VDO3 to receiver cabling above the drop-down roof panel.



3 On-Screen configuration:

Select Auto-Guide >



Auto-Guide(again) >



System >



Signal



4 Select:
RTK network as signal type > External
Modem as Modem type >

Choose the correct Baud rate for your
corresponding external modem >
Data parity None >
Signal Format RTCM3.1.

